

HS RF-SEMI EX

 II 2G IIB T4

 II 2D T4

For operation in explosive atmospheres

- zone 1. (Gas)
- zone 21. (Dust)


Characterised by the product mark



Zone 1



Zone 21



This supplement for the instruction manual of the basic product indicates that the construction of the product is in accordance with the safety precautions and that the product is suited for operation in explosive atmospheres - zone1, generated by gases, vapours or mist in apparatus group IIB and in temperature class T4.

Or - zone 21 concerning dust in the temperature class T4.

The explosion proved construction is characterised by the following product mark:

 II 2G IIB T4 (Gas)

 II 2D T4 (Dust)

Safety precautions:

Dust, dirt, painting, acid, washout, overload and impacts can lead to a reduction or a total breaking of the earthing of electric/ elektrostatic energy. The permanent compliance with the safety-related and technical stipulations, such as e.g. control of the wheel(s) with conductance concerning the above functional disturbances, is the responsibility of the user exclusively.

Additional wheels:

The explosion proved stacker will have at least one anti-static wheel with a separate item no.

When reordering an anti-static wheel, please state product type and whether the wheel is used as steering or fork wheel.


EU DECLARATION OF CONFORMANCE


Manufacturer: **Logitrans A/S**
Hillerupvej 35
DK-6760 Ribe
Denmark



It is hereby declared that:

Machine: Product group: Stackers - zone 1

Type: HS RF-SEMI EX  II 2G IIB T4 (Gas)

Type approval: PTB 03 ATEX 5001x
Logitrans ATEX D130 (Dust)  II 2D T4 (Dust)

Year of manufacture/
Serial No.:

- a)** Has been manufactured in conformance with the stipulations of the
- **COUNCIL DIRECTIVE no. 98/37/EC**
 - **ATEX DIRECTIVE no. 94/9/EF**
- b)** Has been manufactured in conformance with the stipulations of the standard:
- **EN-1757-1** • **EN 1755**
 - **EN 50014** • **EN 1127-1**
- National Danish standards**
Fire technical instruction no. 19
AT instruction C.0.9
(Working Environment Service)

Name: Erling Pedersen

Position: Product manager

Company: Logitrans A/S

Signature: 

Distributor:

Product type declaration of:
14.02.2006

The stacker is further characterised by the following product mark:

When inserting and withdrawing into and out of pallets, avoid dragging the stacker against sharp edges.

Periodic safety inspection

Safety inspection should be performed by the supplier or other qualified persons at least once each year, unless local regulations state otherwise.

Such inspection shall be performed in accordance with the instruction manual. Test instructions and test forms are available from the distributor.